

Serial to Ethernet Converter with Dual Ethernet Switch

SSE232-2ETH-IA3



The SSE232-2ETH-IA3 Industrial will allow you to connect your devices with RS232/485/422 communication to an Ethernet TCP/IP network with Industrial Switch with 2 RJ45 ports, for an easy and fast integration in panels.

★ FEATURES

- Converts serial ports to Ethernet TCP/IP or UDP/UP
- 2-Port Ethernet RJ45 Switch
- Up to 4 serial ports RS232 / RS485 / RS422
- Serial port transparent Tunnel
- Ethernet I/O, with built-in digital inputs and outputs
- Multi-drop over Ethernet. One server, many clients.

★ GENERAL SPECIFICATIONS

- DIN rail mounting, temperature-resistant Industrial Case.
- Wide range power supply (10 to 30 Volts DC).
- Industrial pluggable terminal blocks.
- Automated recovery in case of lost communication.
- COM Port redirector software.
- Digital Input Notification through SNMP traps. SNMP Digital Outputs control.
- Easy Web browser configuration.
- Software for searching Exemys devices on the network.


✓ APPLICATIONS

- PLC's and SCADA systems.
- Industrial Automation.
- Remote monitoring.
- Access Control and Security Systems



The SSE232-2ETH-IA3 is a device that can connect any serial equipment (RS232/485/422) to an Ethernet TCP/IP network with 2 ports switch

Remote Monitoring



Serial to Ethernet Converter

SSE232-2ETH-IA3



TECHNICAL FEATURES

- **Network Protocols:** TCP / IP, UDP / IP, DNS, HTTP, DHCP, ICMP, ARP, SNMP.
- **Network Port:** 2 Ethernet Ports 10/100 baseT, RJ45 Connector.
- **Serial Protocol:** Transparent.
- **Serial Port:** Up to 4 RS232/RS485 in pluggable terminal blocks
- **Supported Devices:** Any RS-232 / RS-485 device
- **Flow Control:** RTS / CTS.
- **Management:** HTTP Server, password protected.
- **Firmware upgrade:** Via WEB
- **Indicators:** Network LED , Link LED.
- **Dimensions:** 100 mm x 22,5 mm x 112 mm (H x W x D).
- **Power Supply** 10 a 30 [Vdc].
- **Current used:** 12 Vdc 70 [mA] / 24 Vdc 40 [mA].
- **Temperature:** Operation temperature: -15 to 65 °C.
Storage temperature: -40 to 75 °C.
- **Support:** 1-year guarantee. Technical Support included



ORDERING INFORMATION

PART NUMBER	DETAILS
SSE232-4B0-00-2ETH-IA3	4 configurables RS232/RS485 ports - 2 Ethernet ports
SSE232-1C0-00-2ETH-IA3-IS	1 configurable RS232/RS485 Isolated port / RS422 Isolated (half - duplex) 2 Ethernet ports



IEC 60950-1:2005+A1

SISTEMA DE GESTIÓN ISO 9001:2015



GESTION DE LA CALIDAD

RI-9000-6174

Acreditado por OAA

www.exemys.com

For Technical support
support@exemys.com

For Sales
sales@exemys.com

Exemys products are in constant evolution to satisfy our customers needs. For that reason, the specifications and capabilities are subject to change without prior notice. Updated information can be found at www.exemys.com
Copyright © Exemys. All Rights Reserved